

Smart Meter

DDSU666 & DTSU666



Compact and Easy to Instal



Embedded with CT Sampling



Support Export Power and Current Setup



APP Remote Configuration

DDSU666 & DTSU666 Datasheet

Type	DDSU666	DTSU666
Electrical Characteristics		
Application	Single-phase	Three-phase
Nominal Voltage[V]	220, 230, 240	3*220/380
Operating range	0.7~1.2Un	
Rated Current [A]	5	
Max. Current [A]	80	
Frequency/Range [Hz]	50,60/±5	
Power Consumption[W]	≤1	
Max.Instant Consumption[VA]	≤5	
Physical Parameters		
Display	LCD	
Communication	RS485	
Operating Temperature Range	-40°C~60°C	
Ambient Humidity	0-95% Non-condensing	
Ingress Protection	IP54	
Installation method	mounting rack	
Dimensions[H*W*D][mm]	98*36*65	98*72*65
Weight [kg]	0.2	0.4
Applicable Standard	CE, RoHS	

Remark: Apply for Sununo Plus, Suntrio Plus, R5 and AS1 series inverter export limitation control application.

GUANGZHOU SANJING ELECTRIC CO., LTD.

Website: www.saj-electric.com

E-mail: info@saj-electric.com

Add:SAJ Innovation Park, No.9, Lizhishan Road, Science City, Guangzhou, Guangdong, P.R.China.

